

A **NORBIT** Company



← optional
housing &
terminal



► Performance

- Range: 0.5–400 m below transducer
- Seabed penetration: up to 40 m (depending on seabed type and noise)
- Range resolution: up to 5 cm (depending on pulse settings)
- Depth accuracy: 2.5 cm + 0.06% water depth
- Motion compensation: Heave (external sensor data required)

► Transmitter

- Principle: parametric (nonlinear) acoustics
- Frequencies: 100 kHz (HF) / 4–15 kHz (LF)
- Primary Source Level: >238 dB/μPa re 1m
- Acoustic Power: c. 2.3 kW
- Beam width: c. 4° (±2°) for all frequencies
- Pulse type: CW, Ricker
- Pulse width: 0.07–1 ms
- Pulse rate: up to 40 Hz, multi-ping mode

► Data Acquisition

- Digital, 2 channels (LF and HF, "SES3" format)
- Sample rate c. 100 kHz @ 24 bit; resolution <1 cm
- LF sub-bottom data: raw (full-waveform)
- HF data: processed (envelope)

► General & Applications

- First / latest product generation: 2024
- Small boats and vehicles, in- and near shore
- Integration into USV and ASV of all scales
- Remotely controlled and autonomous operation

► System Components

- Deck unit (transceiver electronics, IP20):
Housing ½ 19 inch / 3 U, rack-mountable
W 24 cm × D 36 cm × H 14 cm / c. 6.5 kg
- Transducer (no depth rating):
W 34 cm × D 26 cm × H 8 cm / c. 9 kg (w/o cable)
cable length 7–15 m, moulded to transducer
- System control PC (not included):
MS Windows® based

► Optional Features

- Water-proof Subconn® transducer connector
- Transducer mounting kit with shock absorbers
- Deck unit with transducer socket
- External AC power adapter (100–240 V AC)
- SESWIN extended remote-control

► Power Supply Requirements

- 24 V (20–30 V) DC
- Power consumption: typ. 50 W / max. 100 W
- Power-on inrush current: max. 15 A

► Software

- SESWIN data acquisition software
- SES-Convert SEG-Y/XTF data export
- SES-NetView remote display
- ISE post-processing software (option)

